


DK SERIES

DK861LR4


86" 3500 nits UHD Single-sided Ultra-High Brightness Outdoor Kiosk



LOW POWER
CONSUMPTION



SUNLIGHT
VIEWABLE IMAGE



VANDAL
RESISTANT



VIEWABLE WITH
POLARIZED LENSES



WEATHER
PROOF

FOR MORE INFORMATION

For more information about DynaScan, visit our website at www.dynascandisplay.com. Copyright © DynaScan Technology Inc. All rights reserved. All specifications and descriptions are subject to change without notice. Reproduction without permission is prohibited.

DynaScan

SPECIFICATION

MODEL	DK861LR4
DISPLAY	<p>LCD Panel Size 85.6" inches LCD</p> <p>Native Resolution 3840 x 2160</p> <p>Backlight LED</p> <p>Brightness 3,500 nits</p> <p>Light Lifetime (Typ.) 100,000 hrs</p> <p>Contrast Ratio 3000 : 1</p> <p>Color Depth 10 bits</p> <p>Viewing Angle 178° / 178°</p> <p>Blackening Defect Free Up to 110°C (230°F)</p> <p>Polarized Sunglasses Support Yes</p> <p>Touch Function (Optional) P-Cap touch</p>
POWER	<p>Power Supply Internal</p> <p>Rated Voltage 200-240V ~ 50/60HZ</p> <p>Power On Mode (Typ./ Max) 650W / 1700W [TBD]</p>
MECHANICAL SPECS	<p>Bezel Width (T/B/L/R) 95.2 / 106.7 / 134.4 / 134.4 mm</p> <p>Cabinet Color Black</p> <p>Dimension (LxHxD, w/o stand) 1338.0 x 2174.0 x 202.0 mm</p> <p>Weight < 350 kg [TBD]</p> <p>Orientation Portrait</p> <p>Reserved Space for Optional Player Yes</p> <p>High Security Lock Yes</p>
USER INTERFACE	<p>Language English</p> <p>Support SNMP (Up to V3.0) Yes</p> <p>Local Dimming Control Yes</p> <p>Ambient Light Sensor Yes</p> <p>Power On/Off Scheduling Yes</p> <p>Internal Temperature Sensor Yes</p> <p>Backup Player Build-in Yes</p>
INPUT	<p>HDMI x3 (2160p)</p> <p>Display Port x1</p> <p>USB 3.0 x1</p> <p>Micro SD Slot x1</p>
OUTPUT	Audio x1
EXTERNAL CONTROL	<p>RS-232 In x1</p> <p>RJ-45 x2 (LAN)</p>
ENVIRONMENT	<p>Operating Temperature -30° C ~ 50° C</p> <p>Storage Temperature -20° C ~ 60° C</p> <p>Humidity 10% ~ 100% RH Non-condensing</p> <p>Environmental Rating IP56 / IK10 / ASTM G155</p>
CERTIFICATION	CE / FCC / UL / ROHS

DIMENSIONS

